

# KHC-600D

# Pipe Hole Cutting Machine

# Features and Benefits

Automatic oxy-fuel pipe cutter
Automatically bevel cuts or straight cuts holes into pipe.

# Infinite rotational gas manifold

Tangle-free, infinite rotation gas manifold eliminates tension to the torch during cutting, ensuring accurate, sharp & clean cuts.

# H-lever handle torch


Height is automatically maintained to work distance based on trigonometry function of H-lever; very easy setup with just two adjustments.

## On/Off drive clutch

Worm gear with low transmission ratio.

# Flat plate circle cutting

Can be used for circle cutting on flat plate.



Smal diameter pipe fixture

Overhang cutting fixture

# T-Joint pipe hole cutting

## High quality cuts with easy operation

The distance between the cutting nozzle and the plate is automatically, mechanically maintained, ensuring high quality cuts. Very easy to setup with just two adjustments. Also, an infinite rotation gas manifold with slip coupling is used on the main gas connection, keeping hoses from becoming tangled during operation.



The KHC-600D is ideally suited for cutting high precision T- joint circles including any hole that crosses the side of the pipe for piping systems, high pressure vessels and heat exchangers. Developed with KOIKE Advanced Technology, the KHC-600D is a compact design that is light weight and easy to operate. In addition to cutting circles and bevel in flat plate, the machine can cut holes in vessels from the inside or outside.

Optional accessories		
Accessory	Stock #	Description
Small diameter pipe fixture	90123	Fixture to small diameter pipes
Overhang cutting fixture	90125	Enables hole cutting near the end of pipe
Transformer AC230V - 42V	222.002.207	For 42V models

Specification	KHC-600D	
Cutting thickness	5 -50 mm	
Torch rotation speed	0.12 ~ 1.2 rpm	
Cutting diameter	Ø 80 ~ 600 mm	
Torch up/down stroke	0 ~ 100 mm	
Torch revolving radius	r 40 ~ 300 mm	
Bevel angle	0 ~ 45°	
Speed control	Control with dial operation	
Pipe ratio branch : main	1:2 and above	
Input power	AC 42V	
Dimension	L1050 x W500 x H760 mm	
Weight	26 kg (incl. support leg)	

Types	
Model	Stock #
KHC-600D 42V	90122

Scope of delivery		
Machine body including support leg		
Cutting nozzles (102HC or 106HC, size #0, 1, 2)		
Power cable		
Standard tool set		
Operation manual		





KOIKE is the world's leading manufacturer of the most extensive cutting product line for oxy-fuel, plasma, and laser cutting machines.

Request your catalogue via: info@koike-europe.com



# **EMEA Sales and Service Offices**

# FRANCE

KOIKE France S.A.R.L. ZAC de la Vallee de L'aunelle RN Cellules C1 à C4 59144 Wargnies-Le-Grand Office: +33 327304343

#### GERMANY

KOIKE EUROPE B.V. Germany Branch Office Im Löchel 2 35423 Lich-Eberstadt Office: +49 6004916930

# ITALY

KOIKE ITALIA Srl Via Papa Giovanni XXIII, n 45 20053 - Rodano (Milano) Office: +39 0295328717

# UAE

KOIKE MIDDLE EAST FZE SAIF Zone Sharjah - UAE P.O. Box 122978 Office: +971 561177615

#### THE NETHERLANDS

KOIKE EUROPE B.V. Grote Tocht 19 1507 CG Zaandam

+31 (0)75 612 72 27 Т +31 (0)75 612 34 61 F

info@koike-europe.com www.koike-europe.com